

Cold-Water High Pressure Cleaners

KÄRCHER HD 7/18 C

This cold-water pressure washer with a long life three-phase motor is the ideal entry-level model for commercial end customers.

The upright HD 7/18 C boasts impressive mobility, compactness and height-adjustable shaped aluminium push handle. The advantage of the push handle is that it can easily be adjusted to the operator's height without using tools. In the extended position, the unit's generous stowage facilities ensure that accessories are always ready to hand and put away safely. When retracted, this handy unit can be stowed easily in any estate care or service vehicle.

The washer boasts familiar KÄRCHER features such as a full shock-resistant plastic covering that protects the high-pressure pump and the motor from damage and soiling. Other very good features are an electric cable retractor (with plug lock) and a nozzle compartment arranged practically on the back of the unit.

The cleaner comes with a three-way nozzle that enables the water jet to be adjusted quickly and easily. You can choose between a high-pressure pencil jet, a high-pressure fan jet (25°) and a low-pressure fan jet (40°) is used for dispensing cleaning agent. The cleaning agent metering valve enables cleaning agent to be mixed continuously with the high-pressure jet.

The large-volume oil container, which is very important for ensuring that the unit is always adequately lubricated, can be checked very easily from outside through an oil level inspection glass. The three-piston axial pump with stainless steel pistons and a brass cylinder head guarantees a long service life and low susceptibility to faults. The special feature of this newly developed pump is that both the water inlet and the high-pressure outlet are made of brass, which makes them highly resistant to fracture and corrosion.

STANDARD ACCESSORIES

- Anti-twist system (AVS)
- High-pressure hose 10 m
- Servo Control
- Spray lance 850 mm
- Stainless steel spray lance 850 mm
- Trigger gun Easy Press
- Trigger gun with soft grip
- Triple nozzle (0°/25°/40°) Manual
- Triple nozzle/Power nozzle Manual



Part no. 1.151-601.0

TECHNICAL SPECIFICATIONS

Dimensions (L x W x H)	375 x 360 x 935 mm
Connected load	5 kW
Quantity of current phase	3 Ph
Pressure	20-175/2-17,5 bar/MPa
Water flow rate	240-700 l/h
Frequency	50 Hz
Weight	29 kg
Voltage	400 V
Max. Water feed temperature	up to 60 °C